



EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 26-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
Design Life as per Eurobat Standards


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	26Ah
	10 Hour rate	23.7Ah
	5 Hour rate	20.5Ah
Internal Resistance (25°C, 100% Charge)		≤ 12 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		300A (5sec)
Maximum Charging current		9.6A
Short Circuit Current		1200A
Charge Methods Constant Voltage Charge 77°F (25°C) - Cycle use		14.4 to 14.7V Temp. Compensation -30mV/°C
Charge methods Constant Voltage Charge 77°F (25°C) - Standby Use		13.4 to 13.8V Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
166 mm	175 mm	125mm	125 mm	8.1 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	95.0	64.0	48.0	28.5	16.0	6.74	4.47	2.52	1.32
1.65	90.1	60.9	45.9	27.4	15.4	6.53	4.36	2.47	1.31
1.70	84.9	57.8	43.7	26.2	14.8	6.30	4.24	2.42	1.31
1.75	79.7	54.5	41.1	24.9	14.2	6.05	4.10	2.37	1.30
1.80	74.3	51.3	39.1	23.6	13.5	5.78	3.95	2.31	1.28

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	185	121	90.0	55.0	31.7	13.4	8.54	5.38	2.78
1.65	173	114	85.1	52.3	30.3	13.1	8.39	5.35	2.77
1.70	161	107	80.2	49.4	28.9	12.5	8.22	5.30	2.73
1.75	151	99.7	75.2	46.6	27.5	12.0	8.03	5.18	2.68
1.80	139	92.7	70.3	43.7	26.0	11.4	7.83	5.12	2.62




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 26-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2